

Fermo VIS

Single head cutting-off
machines



Stop gauge system with profile support, positioning of the stop via handwheel and reading of position on the digital readout.

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is
reserved.



VIS digital reader

Digital display that allows reprogramming of machine 0, indicating the stop positioning dimension, which corresponds to the length of the workpiece to be cut.



Handwheel

By means of the handwheel, the stop is brought into position.



Reference stop

Carriage running on ball bushing actuated by mechanically controlled kinematics, which allows, referring to the centre of the blade, the realization of the length of the workpiece to be cut.

FERMO VIS / SINGLE HEAD CUTTING-OFF MACHINES

MACHINE CHARACTERISTICS

Effective stroke (according to model) (mm)	3.780 ; 5.780
--	---------------

Positioning tolerance (mm)	± 0,5 (*)
----------------------------	-----------

(*) The machine does not have a thermal deformation compensation system. The reported information refers to a temperature of 20°C

Included ● Available ○

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.