



## **Roto**

Support equipment



Vertical wrapping machine for door/window frames. The rotary mounting base is complete with roller conveyor for easier handling of heavy or large size pieces. The machine requires only one operator.



### Doors clamping

Stem movement allows pneumatic descent to ensure proper locking of the frame.



### Double reel housing

A dual carriage system allows microfilm and bubble wrap reels to be housed separately to speed up automatic packing operations.



### Control and footswitch assembly

The central console constructed of thermoformed ABS allows the user to manage functions such as: plate rotation speed, packing reel rise speed selection, frame locking, unwinding direction selection, manual reel change button.



### Door sliding roller conveyor

A fixed roller conveyor allows horizontal translation of the frame by stem-mounted rollers that ensure smoothness and ease of movement.


**ROTO / SUPPORT EQUIPMENT**
**CHARACTERISTICS**

|   |           |
|---|-----------|
| Control footswitch  | ●         |
| Control panel with display for viewing and setting machining parameters | ●         |
| Semi-automatic rotary table   | ●         |
| Carriage for double reel of bubble wrap/microfilm                       | ●         |
| Rotating bench (mm)   | Ø = 1.800 |
| Table rotation speed (rpm)  | 4 ÷ 12    |
| Carriage up/down speed (m/min)  | 1,3 ÷ 3,5 |
| Air consumption (NI/cycle)  | 18        |
| Installed power (kW)  | 1,9       |

**PACKABLE WINDOW**

|                            |             |
|----------------------------|-------------|
| Height (mm)                | 600 ÷ 2.800 |
| Width (mm)                 | 320 ÷ 1.800 |
| Thickness (mm)             | 40 ÷ 380    |
| Window maximum weight (kg) | 80          |

**REEL (FILM) DIMENSIONS**

|                                   |         |
|-----------------------------------|---------|
| Outer diameter, maximum size (mm) | 300     |
| Inner diameter (mm)               | 76      |
| Reel height (mm)                  | 500     |
| Film thickness (μ)                | 17 ÷ 35 |
| Maximum weight (kg)               | 20      |

**REEL (PLURIBALL) DIMENSIONS**

|                                   |       |
|-----------------------------------|-------|
| Outer diameter, maximum size (mm) | 1.000 |
| Inner diameter (mm)               | 76    |
| Reel height (mm)                  | 500   |
| Maximum weight (kg)               | 12    |

Included ● Available ○