



## **SPIN 4**

Professional trolleys



Gasket trolley. Reel with brake and gasket-guide ensure troublefree gasket unwinding. It is equipped with a quick gasket roll change system.



### Reel holder

A system of adjustable and extendable reel holders allows adaptation to the various sizes and types of reels that will be housed.



### Reel locking clutch

The reel with clutch counteracts the unwinding phase without the possibility of running into mishaps.



### Pivoting wheels

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.

**SPIN 4 / PROFESSIONAL TROLLEYS****CHARACTERISTICS**

|  |       |
|--|-------|
| Minimum coil reel diameter (mm)                      | 110   |
| Maximum reel diameter (mm)                           | 720   |
| Maximum reels width (mm)                             | 250   |
| Reel rotation clutch                                 | ●     |
| Number of removable reels (according to model)       | 4     |
| Fixture locking device complete with clutch          | ●     |
| 4 swivel casters, 2 of which have locking stops (mm) | Ø=125 |
| Length (mm)  | 825   |
| Width (mm)   | 970   |
| Height (mm)  | 1.520 |
| Load capacity (kg)                                   | 60    |
| Weight (kg)  | 44    |

Included ● Available ○