

## ***Unloading roller conveyor***

Single head cutting-off machines



Tubular steel construction with adjustable mounting feet and PVC covered steel rolls. In the version with rolls size 240 mm, roller conveyor length is 3.500 mm; with rolls size 440 mm, roller conveyor length is 4.000 mm.

**Emmegi S.p.A.**  
Via Archimede, 10  
41019 - Limidi di Soliera (MO)  
ITALY

Tel +39 059 895411  
Fax +39 059 566286  
P.Iva/C.Fisc 01978870366  
[info@emmegi.com](mailto:info@emmegi.com)  
[www.emmegi.com](http://www.emmegi.com)

The right to make technical alterations is reserved.

**Stop**

Carriage running on ball bushing actuated by mechanically controlled kinematics, which allows, referring to the centre of the blade, the realization of the length of the workpiece to be cut.

**Side view**

Through special steel bracket, the mechanical connection to the cutting machine is made precisely and rigidly.

**Roller**

PVC-coated steel rollers of 240/440 mm that allow the profile to slide effectively, preventing surface damage.

## UNLOADING ROLLER CONVEYOR / SINGLE HEAD CUTTING-OFF MACHINES

## CHARACTERISTICS

|   |     |
|---|-----|
| Maximum load capacity (according to model) - roller conveyor L=3500 mm, rollers L=240 mm (kg) | 100 |
| Maximum load capacity (according to model) - roller conveyor L=4000 mm, rollers L=440 mm (kg) | 250 |

Included ● Available ○

emmegi S.p.A.  
Via Archimede, 10  
41019 - Limidi di Soliera (MO)  
ITALY

Tel +39 059 895411  
Fax +39 059 566286  
P.Iva/C.Fisc 01978870366  
info@emmegi.com  
www.emmegi.com

The right to make technical alterations is reserved.