







Single-head, descending blade cutting-off machine with left loading side, rotation of the cutting head to 45° (left and right) and manual tilting by 45° referred to the horizontal axis.

TECHNICAL SHEET

01/12/2025





Cutting zone

The sturdy cast-iron horizontal support surface, with its vertical square rigidly coupled to it, forms the workpiece clamping area; it features a large bearing surface for optimum clamping of workpieces.



Vices

The machine is equipped with horizontal vices assembly which, in the S version, are pneumatically actuated, while in the M version are manually actuated



Control

The manual actuator that characterises blade descent is equipped with a mechanical safety system aimed at preventing any accidental movement. At the same time, it determines the gradual exit of the blade itself. Angular positioning of the head is done by rotating the horizontal plane with mechanical snap lock for 45° (right and left) and manual locking for intermediate angles.







MSP 400 / SINGLE HEAD CUTTING-OFF MACHINES


BLADE

Made of Widia (mm) Ø = 400


BLADE FEED

Manual

CUTTING DIAGRAM



CUTTING UNIT TILTING



Mechanical adjustment of intermediate angles

CUTTING AREA PROTECTION

Local, mechanically controlled

Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com The right to make technical alterations is reserved.





TECHNICAL SHEET

11/12/2025

2,2

LUBRICATION SYSTEM Micro-mist lubrication system with water and oil emulsion WORKPIECE LOCKING Pair of pneumatic horizontal vices MOTOR Three-phase brake motor Brake intervention time (s)

Included ● Available ○

Power (kW)