



## ***TRANSIT KT***

Professional trolleys



Trolley for transportation and storage of casement and finished door/ window frames. The resting base has rollers for easier handling of heavy or large size pieces.

**Side contact surfaces**

All contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.

**Pivoting wheels**

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.

**Door sliding roller conveyor**

A fixed roller conveyor allows horizontal translation of the frame by stem-mounted rollers that ensure smoothness and ease of movement.

**TRANSIT KT / PROFESSIONAL TROLLEYS****CHARACTERISTICS**

Compartment depth (mm)	1.160
Preparation for K-Rail track	●
Number and width of compartments according to model	●
Base with roller conveyor	●
Soft PVC contact surface	●
Handle for moving	●
Wheels (mm) including two swivel wheels with brakes	Ø = 150

**WEIGHT (DEPENDING ON MODEL)**

TRANSIT KT 6-100 mm (kg)	105
TRANSIT KT 10-100 mm (kg)	160
TRANSIT KT 15-100 mm (kg)	225
TRANSIT KT 5-130 mm (kg)	95
TRANSIT KT 10-130 mm (kg)	160
TRANSIT KT 15-130 mm (kg)	230
TRANSIT KT 5-160 mm (kg)	100
TRANSIT KT 10-160 mm (kg)	190

**MAXIMUM LOAD CAPACITY (ACCORDING TO MODEL)**

TRANSIT KT 6-100 mm (kg)	600
TRANSIT KT 10-100 mm (kg)	740
TRANSIT KT 15-100 mm (kg)	675
TRANSIT KT 5-130 mm (kg)	500
TRANSIT KT 10-130 mm (kg)	740
TRANSIT KT 15-130 mm (kg)	670
TRANSIT KT 5-160 mm (kg)	500
TRANSIT KT 10-160 mm (kg)	710

Included ● Available ○