

Trolley designed for transportation and storage of frames, sashes and casements.



Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY

Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com The right to make technical alterations is reserved.

🛆 emmegi 🗄

TECHNICAL SHEET

14/09/2025



Contact surfaces

All side and lower contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.



Pivoting wheels

Equipped with 4 pivoting wheels with brakes, they ensure a high degree of mobility and easy handling of the object. Locking the braking units allows their position to be fixed near different work areas.



Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY

Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com The right to make technical alterations is reserved.



CHARACTERISTICS	
Compartment depth (mm)	930
Compartment width (mm)	100
Vertical support, height (mm)	1.045
Number of compartments	10
Soft PVC contact surface	•
Wide supporting base	•
Handle for moving	•
4 swivel casters, 2 of which have locking stops (mm)	Ø = 125
Length (mm)	1.540
Width (mm)	1.050
Height (mm)	1.305
Weight (kg)	90
Load capacity (kg)	500

Included
Available



Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY

Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com The right to make technical alterations is reserved.